

## rpm measuring instrument

testo 460 – Pocket-sized  
non-contact rpm measurement

---

Optical rpm measurement with LED measurement spot marking

---

Min./max. values

---

Display illumination

---

Protective cap for safe storage

---

Incl. wrist strap and belt holder

---



Illustration 1/1

The especially handy, pocket-sized rpm measuring instrument testo 460 optically measures rpm, e.g. on ventilators and shafts. The ideal distance to the measurement object is between 10 and 40 cm. Simply attach a reflective marker (optional) to the measurement object, point the visible measurement spot at the reflective marker, and measure. Min./max. values are directly displayed at the press of a button.

The Hold-button allows particularly convenient reading of the measurement values. The illuminated display enables easy read-out of the measurement values even in bad lighting. testo 460 is very small, handy and easy to operate. The clip-on protective cap, wrist strap and a belt holder provide safe storage, ensuring an especially long working life.

## Technical data / Accessories

### testo 460

testo 460 measuring instrument for rpm  
incl. protection cap, batteries, belt holder  
and calibration protocol

Part no. 0560 0460



#### Sensor type **optical**

|                      |   |
|----------------------|---|
| Measuring range      | 100 to 29999 rpm  |
| Accuracy<br>±1 digit | ±(0.02 % of mv)   |
| Resolution           | 0.1 rpm (100 to 999.9 rpm)<br>1 rpm (1000 to 29999 rpm) |

#### General technical data

|                       |  |
|-----------------------|--|
| Selectable units      | rpm, rps                                     |
| Measuring rate        | 0.5 s  |
| Storage temperature   | -40 to +70 °C                                |
| Operating temperature | 0 to +50 °C                                  |
| Battery type          | 2 AAA micro batteries                        |
| Battery life          | 20 h (average, without display illumination) |
| Weight                | 85 g (incl. battery and protective cap)      |
| Dimensions            | 119 x 46 x 25 mm (incl. protective cap)      |
| Protection class      | IP40   |
| Warranty              | 2 years                                      |

0981 9784/msp/A/01.2017

### Accessories

### Part no.

#### Accessories for measuring instrument

|  |           |  |
|--|-----------|--|
| Reflectors, self-adhesive (1 pack = 5 off, each 150 mm long)                               | 0554 0493 |  |
| Belt holder  | 0516 4007 |  |
| ISO calibration certificate/rpm, Calibration points freely selectable from 10 to 99500 rpm | 0520 0114 |  |

Subject to change without notice.

### Authorized & Exclusive Distributor:



**Enviro Engineering General Trading LLC**  
Instrumentation, Automation & Networking

Office # 808, 8th Floor, International Business Tower, Al A'amal St.,  
Business Bay, P.O. Box 41454, Dubai, United Arab Emirates  
Tel. #: +971 4 4201188 | Fax #: +971 4 4547789  
www.enviroegt.com | info@enviroegt.com

OFFICE HOURS:  
Saturday to Wednesday: 8:30 AM – 5:00 PM  
Thursday: 8:30 AM – 1:30 PM

